

Breath Alcohol Testers



Product Catalog

Contents

INTRODUCTION TO BREATH ALCOHOL ANALYZERS	3
<i>Principles of Testing.....</i>	<i>3</i>
 BREATH ALCOHOL ANALYZERS	 4
BAT-0340 – GENERAL ACCURACY LED BREATH ALCOHOL TESTER	4
BAT-0360 – GENERAL ACCURACY BREATH ALCOHOL TESTER.....	4
BAT-0370 – GENERAL ACCURACY LCD DISPLAY BREATH ALCOHOL TESTER W/TORCH	5
BAT-0380 – GENERAL ACCURACY LCD DISPLAY BREATH ALCOHOL TESTER	5
BAT-0382 – GENERAL ACCURACY BREATH ALCOHOL TESTER WITH CLOCK	6
BAT-0383 – GENERAL ACCURACY DIGITAL BREATH ALCOHOL TESTER	6
BAT-0389 / BAT-1389 – MEDIUM ACCURACY DIGITAL TESTER WITH CLOCK	7
BAT-0395 – MEDIUM ACCURACY DIGITAL BREATH ALCOHOL TESTER	7
BAT-0397 – HIGH ACCURACY DIGITAL BREATH ALCOHOL TESTER.....	8
BAT-0701 – GENERAL ACCURACY LED BREATH ALCOHOL TESTER WITH TORCH.....	8
BAT-0702 – MEDIUM ACCURACY DIGITAL BREATH ALCOHOL TESTER WITH CLOCK	9
BAT-0703 – MEDIUM ACCURACY DIGITAL BREATH ALCOHOL TESTER WITH CLOCK	9
BAT-0707 – GENERAL ACCURACY LED BREATH ALCOHOL TESTER WITH TORCH.....	10
BAT-0708 – HIGH ACCURACY DIGITAL BREATH ALCOHOL TESTER.....	10
BAT-0709 – GENERAL ACCURACY LED BREATH ALCOHOL TESTER WITH CLOCK AND TORCH.....	11
BAT-0803 – GENERAL ACCURACY LED BREATH ALCOHOL TESTER WITH CLOCK AND TORCH.....	11
BAT-0880 – HIGH ACCURACY DIGITAL BREATH ALCOHOL TESTER.....	12
BAT-0882 – GENERAL ACCURACY LCD BREATH ALCOHOL TESTER	12
BAT-0883 – GENERAL ACCURACY LED BREATH ALCOHOL TESTER	13
BAT-0889 – HIGH ACCURACY DIGITAL BREATH ALCOHOL TESTER WITH CLOCK	13
BAT-0895 – HIGH ACCURACY DIGITAL BREATH ALCOHOL TESTER.....	14
BAT-2718 – HIGH ACCURACY DIGITAL BREATH ALCOHOL TESTER WITH TEMPERATURE SENSOR, CLOCK	14

Introduction to Breath Alcohol Analyzers

Principles of Testing

Alcohol that a person drinks eventually shows up in the breath. After getting absorbed from the mouth, throat, stomach and intestines into the bloodstream, the blood moves through the lungs where a portion is evaporated and exhaled.

Alcohol is not digested upon absorption, nor chemically changed in the bloodstream. As the blood goes through the lungs, some of the alcohol moves across the membranes of the lung's air sacs (alveoli) and into the air. The concentration of the alcohol in the alveolar air is related to the concentration of the alcohol in the blood. As the alcohol in the alveolar air is exhaled, it can be detected by the breath alcohol testing device. Instead of having to draw a driver's blood to test the alcohol level, an officer can test the driver's breath on the spot and instantly know if there is a reason to arrest the driver.

Because the alcohol concentration in the breath is related to that in the blood, you can figure the Blood Alcohol Content (BAC) by measuring alcohol on the breath. The ratio of breath alcohol to blood alcohol is 2,100:1. This means that 2,100 milliliters (ml) of alveolar will contain the same amount of alcohol as 1 ml of blood.

For many years, the legal standard for drunkenness across the United States was 0.10, but many states have now adopted the 0.08 standard. The federal government has pushed states to lower the legal limit. The American Medical Association says that a person can become impaired when the blood alcohol level hits 0.05. If a person's BAC measures 0.08, it means that there are 0.08 grams of alcohol per 100 ml of blood.

Display Interpretation

Jade Connections carries many different types of Breath Analyzers. They vary by features, displays, availability of backlights, etc. Most testers have three different stats that they report. Unless otherwise stated in the specifications below, the meaning of these states is:

Safe	< 0.02 % BAC
Caution	0.02% - 0.05% BAC
Danger	> 0.05% BAC

Breath Alcohol Analyzers

BAT-0340 – General Accuracy LED Breath Alcohol Tester



A small hand-held tester with LED indicators:

Green (safe): < 0.02 %; Yellow (caution): 0.02–0.05%; Red (danger): > 0.05 % BAC.

Comes with a built-in flashlight / torch.
Color: Black

Specifications

Display Type: LED
Sensor Type: General accuracy semiconductor
Warm-up Time: < 10 seconds
Response Time: < 5 seconds
Blowing opportunity time: 10 seconds
Measuring Range: 0.02 – 0.05 % BAC
Test Accuracy: 0.02% BAC
Fast reset, beep/buzzer
Available Colors: Black
Operating Temperature: 10 – 40 C
Environmental Humidity: 40 – 90 %
Batteries: 2 x AAA Alkaline (not included)

Certifications

CE, RoHS

Warranty Terms

12 months after delivery from factory. Defective units will be replaced free, customer only pays return shipping charges.

Packaging

Device Size: 85.2 x 39.2 x 20 mm, 40g
Package Dimensions: 14.9 x 9.7 x 3.3 cm
Carton Size: 50.5 x 36.5 x 32 cm , 100 pcs/ctn
Carton Volume / Gross Weight: 12 kg / 8.5 kg

BAT-0360 – General Accuracy Breath Alcohol Tester



General Accuracy hand-held tester with LED indicators:

Green: < 0.02; Yellow: 0.02 – 0.05; Red: > 0.05 % BAC.

Comes with a built-in flashlight / torch. Great for waiters.

Color: Black

Specifications

Display Type: LED
Sensor Type: General Accuracy Semiconductor
Warm-up Time: 10 seconds
Response Time: 5 seconds
Blowing Opportunity Time: 10 seconds
Detection Range: 0.02 – 0.05% BAC
Test Accuracy: 0.02% BAC
Fast reset, beep/buzzer
Low battery indicator
Available Colors: Black
Operating Temperature: 10 – 40 C
Humidity: 40 – 90%
Batteries: 2 x AAA Alkaline (not included)

Certifications

CE, RoHS

Warranty Terms

12 months after delivery from factory. Defective units will be replaced free, customer only pays return shipping charges.

Packaging

Device Size: 73 x 39 x 20 mm
Device Weight: 26g
Packaging Dimensions: 14.9 x 9.7 x 3.3 cm
Carton Size: 50.5 x 36.5 x 32 cm , 100 pcs/ctn
Carton Volume / Gross Weight: 8.5 kg

BAT-0370 – General Accuracy LCD Display Breath Alcohol Tester w/Torch



General Accuracy hand-held tester with face LCD and sound indicators:

Safety: < 0.02; Caution: 0.02 – 0.05; Danger: > 0.05% BAC.

Comes with a built-in flashlight / torch.
Color: White

Specifications

Display Type: LCD Face
Sensor Type: General Accuracy Semiconductor
Warm-up Time: 10 seconds
Response Time: 5 seconds
Detection Range: 0.00 – 0.19% BAC
Test Accuracy: 0.02% BAC
Fast reset, beep/buzzer
Auto Power-off
Low battery indicator
Available Colors: White
Operating Temperature: 10 – 40 C
Humidity: 40 – 90 %
Batteries: 2 x AAA Alkaline (not included)

Certifications

CE, RoHS

Warranty Terms

12 months after delivery from factory. Defective units will be replaced free, customer only pays return shipping charges.

Packaging

Device Size: 100 x 45 x 20 mm
Device Weight: 30g
Packaging Dimensions: 14.9 x 9.7 x 3.3 cm
Carton Size: 50.5 x 36.5 x 32 cm , 100 pcs/ctn
Carton Volume / Gross Weight: 12.0 kg / 9.5 kg

BAT-0380 – General Accuracy LCD Display Breath Alcohol Tester



General Accuracy hand-held tester with face LCD and sound indicators:

Safety: < 0.02; Caution: 0.02 – 0.05; Danger: > 0.05% BAC.

Color: White

Specifications

Display Type: LCD Face
Sensor Type: General Accuracy Semiconductor
Warm-up Time: 10 seconds
Response Time: 5 seconds
Blowing Opportunity Time: 10 seconds
Detection Range: 0.00 – 0.19% BAC
Test Accuracy: 0.02% BAC
Fast reset, beep/buzzer
Auto Power-off
Low battery indicator
Available Colors: White
Operating Temperature: 10 – 40 C
Humidity: 40 – 90 %
Batteries: 2 x AAA Alkaline (not included)

Certifications

CE, RoHS

Warranty Terms

12 months after delivery from factory. Defective units will be replaced free, customer only pays return shipping charges.

Packaging

Device Size: 100 x 45 x 20 mm
Device Weight: 30g
Package Dimensions: 14.9 x 9.7 x 3.3 cm
Carton Size: 50.5 x 36.5 x 32 cm , 100 pcs/ctn
Carton Volume / Gross Weight: 12.0 kg / 9.5 kg

BAT-0382 – General Accuracy Breath Alcohol Tester with Clock



General Accuracy hand-held tester with LED indicators:

Green: < 0.02; Yellow: 0.02 – 0.05; Red: > 0.05% BAC

Built in clock operates as real time clock, alarm, and countdown timer.

Color: White

Specifications

Display Types: BAC: LED, Clock: LCD
 Sensor Type: General Accuracy Semiconductor
 Warm-up Time: 10 seconds
 Response Time: 5 seconds
 Blowing Opportunity Time: 10 seconds
 Detection Range: 0.02 – 0.05% BAC
 Test Accuracy: 0.02% BAC
 Fast reset, beep/buzzer
 Clock functions: real time, alarm, countdown timer
 Available Colors: White
 Operating Temperature: 5 – 40 C
 Batteries: Tester: 2 x AAA Alkaline (not included)
 Clock: 1.5 V AG13 Cell Button (included)

Certifications

CE, RoHS

Warranty Terms

12 months after delivery from factory. Defective units will be replaced free, customer only pays return shipping charges.

Packaging

Device Size: 91 x 31 x 17.5 mm
 Device Weight: 26g
 Packaging Dimensions: 14.9 x 9.7 x 3.3 cm
 Carton Size: 50.5 x 36.5 x 32 cm , 100 pcs/ctn
 Carton Weight: GW/VW: 8.5 kg / 12 kg

BAT-0383 – General Accuracy Digital Breath Alcohol Tester



General Accuracy hand-held tester with digital LCD indicator.

Detection range: 0.00 – 0.40% BAC

Color: White

Specifications

Display Type: Digital LCD
 Sensor Type: General Accuracy Semiconductor
 Warm-up Time: 10 seconds
 Response Time: 3 - 5 seconds
 Detection Range: 0.00 – 0.40% BAC
 Test Accuracy: 0.02% BAC
 Fast reset, beep/buzzer
 Manual power-off
 Low battery indicator
 Available Colors: White
 Operating Temperature: 10 – 40 C
 Humidity: 40 – 90%
 Batteries: 2 x AAA Alkaline (not included)

Certifications

CE, RoHS

Warranty Terms

12 months after delivery from factory. Defective units will be replaced free, customer only pays return shipping charges.

Packaging

Device Size: 105 x 42 x 19 mm
 Device Weight: 30g
 Package Dimensions: 14.9 x 9.7 x 3.3 cm
 Carton Size: 50.5 x 36.5 x 32 cm , 100 pcs/ctn
 Carton Weight: GW/VW: 9.5 kg / 12.0 kg

BAT-0389 / BAT-1389 – Medium Accuracy Digital Tester with Clock



Medium Accuracy hand-held tester with digital LCD.
 Detection range: 0.00 – 0.19% BAC (BAT-0389)
 0.00 – 0.95 mg/l BRAC (BAT-1389)
 Includes built-in clock functions: real-time, alarm, countdown

Includes temperature indicator (-T option)

Color: White

Specifications

Display Type: Digital LCD
 Sensor Type: Medium Accuracy Semiconductor
 Warm-up Time: 10 seconds
 Response Time: 3 - 5 seconds
 Detection Range:
 0.00 – 0.19% BAC, 0.00 – 1.9 g/l (BAT-0389)
 0.00 – 0.95 mg/l BRAC (BAT-1389)
 Blowing Opportunity Time: 10 seconds
 Fast reset, beep/buzzer
 Clock functions: real time, alarm, countdown timer
 Low battery indicator
 Auto power-off
 Available Colors: White
 Operating Temperature: 10 – 40 C
 Humidity: 40 – 90%
 Batteries: Tester: 2 x AAA Alkaline (not included)
 Clock: 1.5V AG13 Cell Button (included)

Certifications

CE, RoHS

Warranty Terms

12 months after delivery from factory. Defective units will be replaced free, customer only pays return shipping charges.

Packaging

Device Size: 98 x 38 x 17.2 mm
 Device Weight: 28g
 Packaging Dimensions: 14.9 x 9.7 x 3.3 cm
 Carton Size: 50.5 x 36.5 x 32 cm , 100 pcs/ctn
 Carton Weight: GW/VW: 9.5 kg / 12.0 kg

BAT-0395 – Medium Accuracy Digital Breath Alcohol Tester



Medium Accuracy hand-held tester with digital LCD indicator.
 Detection range: 0.00 – 0.19% BAC
 0.0 – 1.9 mg/l

Optional orange colored backlight (-S option)

Color: White

Specifications

Display Type: Digital LCD with Optional Backlight
 Sensor Type: Medium Accuracy Semiconductor
 Warm-up Time: 10 seconds
 Response Time: 5 seconds
 Blowing Opportunity Time: 10 seconds
 Detection Range: 0.00 – 0.19% BAC, 0.0 – 1.9 g/l
 Results Display Choices: % BAC, mg/l
 Fast reset, beep/buzzer
 Auto power-off
 Orange backlight (-S option only)
 Low battery indicator
 Available Colors: White
 Operating Temperature: 10 – 40 C
 Humidity: 40 – 90%
 Batteries: 2 x AAA Alkaline (not included)

Certifications

CE, RoHS

Warranty Terms

12 months after delivery from factory. Defective units will be replaced free, customer only pays return shipping charges.

Packaging

Device Size: 98 x 38 x 17.2 mm
 Device Weight: 28g
 Package Dimensions: 14.9 x 9.7 x 3.3 cm
 Carton Size: 50.5 x 36.5 x 32 cm , 100 pcs/ctn
 Carton Weight: GW/VW: 9.5 kg / 12.0 kg

BAT-0702 – Medium Accuracy Digital Breath Alcohol Tester with Clock



Medium Accuracy hand-held tester with digital LCD indicator.
 Detection range: 0.00 – 0.19% BAC
 0.0 – 1.9 g/l

Display Formats: % BAC, mg/l
 Detection Increment: 0.01% BAC / 0.1 mg/l

Color: White

Specifications

Display Type: Digital LCD
 Sensor Type: Medium Accuracy Semiconductor
 Warm-up Time: 10 seconds
 Response Time: 3 - 5 seconds
 Blowing Opportunity Time: 10 seconds
 Detection Range: 0.00 – 0.19% BAC, 0.0 – 1.9 mg/l
 Alert level calibrated
 Fast reset, beep/buzzer
 Low Battery Indicator
 Auto power-off
 Clock functions: 12/24 hour, real time, alarm, count-up and countdown timer.
 Available Colors: White
 Operating Temperature: 10 – 40 C
 Humidity: 40 – 90%
 Batteries: 2 x AAA Alkaline (not included)

Certifications

CE, RoHS

Warranty Terms

12 months after delivery from factory. Defective units will be replaced free, customer only pays return shipping charges.

Packaging

Device Size: 98 x 38 x 17.2 mm
 Device Weight: 28g
 Packaging Dimensions: 14.9 x 9.7 x 3.3 cm
 Carton Size: 50.5 x 36.5 x 32 cm , 100 pcs/ctn
 Carton Weight: GW/VW: 9.5 kg / 12.0 kg

BAT-0703 – Medium Accuracy Digital Breath Alcohol Tester with Clock



Medium Accuracy hand-held tester with digital LCD indicator.
 Detection range: 0.00 – 0.19% BAC
 0.00 – 1.9 g/l

Display Formats: % BAC, mg/l
 Detection Increment: 0.01% BAC / 0.1 g/l

Color: White

Specifications

Display Type: Digital LCD
 Sensor Type: Medium Accuracy Semiconductor
 Warm-up Time: 10 seconds
 Response Time: 5 seconds
 Blowing Opportunity Time: 10 seconds
 Detection Range: 0.00 – 0.19% BAC, 0.0 – 1.9 g/l
 Auto level calibrated
 Fast reset, beep/buzzer
 Low Battery Indicator
 Auto power-off
 Clock functions: 12/24 hour, real time, alarm, count-up and countdown timer.
 Available Colors: White
 Operating Temperature: 10 – 40 C
 Batteries: 2 x AAA Alkaline (not included)

Certifications

CE, RoHS

Warranty Terms

12 months after delivery from factory. Defective units will be replaced free, customer only pays return shipping charges.

Packaging

Device Size: 98 x 38 x 17.2 mm
 Device Weight: 28g
 Packaging Dimensions: 14.9 x 9.7 x 3.3 cm
 Carton Size: 50.5 x 36.5 x 32 cm , 100 pcs/ctn
 Carton Weight: GW/VW: 9.5 kg / 12.0 kg

BAT-0707 – General Accuracy LED Breath Alcohol Tester with Torch



General Accuracy hand-held tester with LED indicators:

Green: Ready (< 0.02); Yellow: 0.02 – 0.05; Red: > 0.05% BAC.

Comes with a built-in flashlight / torch.

Color: White

Specifications

Display Type: LED
 Sensor Type: General Accuracy Semiconductor
 Warm-up Time: 10 seconds
 Response Time: 5 seconds
 Blowing Opportunity Time: 10 seconds
 Detection Range: 0.02 – 0.05% BAC
 Test Accuracy: 0.02% BAC
 Fast Reset, beep/buzzer
 Available Colors: White
 Operating Temperature: 10 – 40 C
 Humidity: 40 – 90 %
 Batteries: 2 x AAA Alkaline (not included)

Certifications

CE, RoHS

Warranty Terms

12 months after delivery from factory.
 Defective units will be replaced free,
 customer only pays return shipping charges.

Packaging

Device Size: 85 x 45 x 20 mm
 Device Weight: 26g
 Packaging Dimensions: 14.9 x 9.7 x 3.3 cm
 Carton Size: 50.5 x 36.5 x 32 cm , 100 pcs/ctn
 Carton Weight: GW/VW: 8.5 kg / 12.0 kg

BAT-0708 – High Accuracy Digital Breath Alcohol Tester



High Accuracy hand-held tester with digital LCD provides precise readings.

Detection range: 0.000 – 0.199% BAC (-A Option)
 0.000 – 1.990 ‰ BAC (-B Option)
 0.000 – 0.995 mg/l (-C Option)

Result Display: % BAC, ‰ BAC, mg/l

Color: Black

Specifications

Display Type: Digital LCD
 Sensor Type: High Accuracy Semiconductor
 Warm-up Time: 10 seconds
 Response Time: 3 - 5 seconds
 Detection Range: 0.000 – 0.199% BAC,
 0.000 – 0.995 mg/l
 Fast reset, beep/buzzer
 Auto power-off
 Low battery indicator
 Available Colors: Black
 Operating Temperature: 10 – 40 C
 Environmental Humidity: 40 – 90%
 Batteries: 2 x AAA Alkaline (not included)

Certifications

CE, RoHS

Warranty Terms

12 months after delivery from factory.
 Defective units will be replaced free,
 customer only pays return shipping charges.

Packaging

Device Size: 106 x 38 x 16 mm
 Device Weight: 28g
 Packaging Dimensions: 14.9 x 9.7 x 3.3 cm
 Carton Size: 50.5 x 36.5 x 32 cm , 100 pcs/ctn
 Carton Weight: GW/VW: 9.5 kg / 12.0 kg

BAT-0709 – General Accuracy LED Breath Alcohol Tester with Clock and Torch



General Accuracy hand-held tester with LED indicators:

Green: Ready (< 0.02); Yellow: 0.02 – 0.05; Red: > 0.05% BAC.

Comes with a built-in flashlight / torch

Color: Black

Specifications

Display Type: Tester: LED, Clock: LCD
 Sensor Type: General Accuracy Semiconductor
 Warm-up Time: 10 seconds
 Response Time: 5 seconds
 Blowing Opportunity Time: 10 seconds
 Detection Range: 0.02 – 0.05% BAC
 Test Accuracy: 0.02% BAC
 Fast reset, beep/buzzer
 Clock functions: real time
 Available Colors: Black
 Operating Temperature: 10 – 40 C
 Humidity: 40 – 90 %
 Batteries: 2 x AAA Alkaline (not included)

Certifications

CE, RoHS

Warranty Terms

12 months after delivery from factory.
 Defective units will be replaced free,
 customer only pays return shipping charges.

Packaging

Device Size: 40 x 23 x 15 mm
 Device Weight: 26g
 Packaging Dimensions: 14.9 x 9.7 x 3.3 cm
 Carton Size: 40 x 40 x 43 cm , 150 pcs/ctn
 Carton Weight: GW/VW: 8.5 kg / 12 kg

BAT-0803 – General Accuracy LED Breath Alcohol Tester with Clock and Torch



General Accuracy hand-held tester with LED indicators:

Green: Ready (< 0.02); Yellow: 0.02 – 0.05; Red: > 0.05% BAC.

Comes with a built-in flashlight / torch.

Color: Grey

Specifications

Display Type: Tester: LED, Clock: LCD
 Sensor Type: General Accuracy Semiconductor
 Warm-up Time: 10 seconds
 Response Time: 5 seconds
 Blowing Opportunity Time: 10 seconds
 Detection Range: 0.02 – 0.05% BAC
 Fast reset, beep/buzzer
 Low battery indicator
 Clock functions: real time
 Available Colors: Grey
 Operating Temperature: 10 – 40 C
 Humidity: 40 – 90 %
 Batteries: 2 x AAA Alkaline (not included)

Certifications

CE, RoHS

Warranty Terms

12 months after delivery from factory.
 Defective units will be replaced free,
 customer only pays return shipping charges.

Packaging

Device Size: 75 x 40 x 23 mm
 Device Weight: 26g
 Packaging Dimensions: 14.9 x 9.7 x 3.3 cm
 Carton Size: 40 x 40 x 43 cm , 150 pcs/ctn
 Carton Weight: GW/VW: 8.5 kg / 12 kg

BAT-0880 – High Accuracy Digital Breath Alcohol Tester



High Accuracy hand-held tester with digital LCD provides precise readings.
 Detection range: 0.000 – 0.199% BAC
 0.000 – 1.990 ‰ BAC
 0.000 – 0.995 mg/l

Result Display: % BAC, ‰ BAC, mg/l

Optional orange colored backlight (-S option)

Color: Black / Red

Specifications

Display Type: Digital LCD with optional backlight
 Sensor Type: High Accuracy Semiconductor
 Warm-up Time: 10 seconds
 Response Time: 3 - 5 seconds
 Detection Range: 0.00 – 0.199% BAC,
 0.000 – 1.995 g/l
 Test Accuracy: One part in a thousand
 Fast reset, beep/buzzer
 Auto power-off
 Orange backlight (-S option only)
 Low battery indicator
 Available Colors: Black/Red Combination
 Operating Temperature: 10 – 40 C
 Environmental Humidity: 40 – 90%
 Batteries: 2 x AAA Alkaline (not included)

Certifications

CE, RoHS

Warranty Terms

12 months after delivery from factory.
 Defective units will be replaced free,
 customer only pays return shipping charges.

Packaging

Device Size: 116 x 45 x 15 mm
 Device Weight: 35 g
 Package Dimensions: 14.9 x 9.7 x 3.3 cm
 Carton Size: 50.5 x 36.5 x 32 cm , 100 pcs/ctn
 Carton Weight: GW/VW: 9.5 kg / 12.0 kg

BAT-0882 – General Accuracy LCD Breath Alcohol Tester



General Accuracy hand-held tester with face LCD indicator.

Safety: < 0.02; Caution: 0.02 – 0.05; Danger: > 0.05% BAC.

Optional green colored backlight (-S option)

Color: Green, White

Specifications

Display Type: LCD Face
 Sensor Type: General Accuracy Semiconductor
 Warm-up Time: 10 seconds
 Response Time: 5 seconds
 Blowing Opportunity Time: 10 seconds
 Detection Range: 0.00 – 0.19% BAC
 Test Accuracy: 0.02% BAC
 Fast reset, beep/buzzer
 Auto power-off
 Green backlight (-S option only)
 Low battery indicator
 Available Colors: Green, White
 Operating Temperature: 10 – 40 C
 Humidity: 40 – 90 %
 Batteries: 2 x AAA Alkaline (not included)

Certifications

CE, RoHS

Warranty Terms

12 months after delivery from factory.
 Defective units will be replaced free, customer
 only pays return shipping charges.

Packaging

Device Size: 100 x 45 x 20 mm
 Device Weight: 30g
 Packaging Dimensions: 14.9 x 9.7 x 3.3 cm
 Carton Size: 50.5 x 36.5 x 32 cm , 100 pcs/ctn
 Carton Weight: GW/VW: 9.5 kg / 12.0 kg

BAT-0883 – General Accuracy LED Breath Alcohol Tester



General accuracy hand-held tester with LED indicators:

Green: < 0.02; Yellow: 0.02 – 0.05; Red: > 0.05% BAC.

Color: Green, White

Specifications

Display Type: LED
 Sensor Type: General Accuracy Semiconductor
 Warm-up Time: 10 seconds
 Response Time: 5 seconds
 Blowing Opportunity Time: 10 seconds
 Detection Range: 0.02 – 0.05% BAC
 Test accuracy: 0.02% BAC
 Fast reset, beep/buzzer
 Low battery indicator
 Available Colors: Green, White
 Operating Temperature: 10 – 40 C
 Humidity: 40 – 90 %
 Batteries: 2 x AAA Alkaline (not included)

Certifications

CE, RoHS

Warranty Terms

12 months after delivery from factory.
 Defective units will be replaced free, customer only pays return shipping charges.

Packaging

Device Size: 102 x 44 x 17.5 mm
 Device Weight: 30g
 Package Dimensions: 14.9 x 9.7 x 3.3 cm
 Carton Size: 50.5 x 36.5 x 32 cm , 100 pcs/ctn
 Carton Weight: GW/VW: 9.5 kg / 12.0 kg

BAT-0889 – High Accuracy Digital Breath Alcohol Tester with Clock



High Accuracy hand-held tester with digital LCD provides precise readings.

Detection range: 0.000 – 0.199% BAC
 0.000 – 1.990 ‰ BAC
 0.000 – 0.995 mg/l

Result Display: % BAC, ‰ BAC, mg/l

Color: White

Specifications

Display Type: Digital LCD
 Sensor Type: High Accuracy Semiconductor
 Warm-up Time: 10 seconds
 Response Time: 3 - 5 seconds
 Detection Range: 0.000 – 0.199% BAC,
 0.000 – 0.995 mg/l
 Test Accuracy: One part in one thousand
 Fast reset, beep/buzzer
 Auto power-off
 Low battery indicator
 Clock functions: real time, alarm, countdown timer
 Available Colors: White
 Operating Temperature: 5 – 40 C
 Batteries: Tester: 2 x AAA Alkaline (not included)
 Clock: 1.5V AG13 Button Battery (included)

Certifications

CE, RoHS

Warranty Terms

12 months after delivery from factory.
 Defective units will be replaced free, customer only pays return shipping charges.

Packaging

Device Size: 100 x 37 x 17 mm
 Device Weight: 30g
 Package Dimensions: 14.9 x 9.7 x 3.3 cm
 Carton Size: 50.5 x 36.5 x 32 cm , 100 pcs/ctn
 Carton Weight: GW/VW: 9.5 kg / 12.0 kg

BAT-0895 – High Accuracy Digital Breath Alcohol Tester



High Accuracy hand-held tester with digital LCD provides precise readings.
 Detection range: 0.000 – 0.199% BAC
 0.000 – 1.990 ‰ BAC
 0.000 – 0.995 mg/l

Result Display: % BAC, ‰ BAC, mg/l

Optional orange colored backlight (-S option)

Color: White

Specifications

Display Type: Digital LCD with Optional Backlight
 Sensor Type: High Accuracy Semiconductor
 Warm-up Time: 10 seconds
 Response Time: 3 - 5 seconds
 Blowing Opportunity Time: 10 seconds
 Detection Range: 0.000 – 0.199% BAC,
 0.000 – 0.995 mg/l
 Test Accuracy: One part in one thousand
 Fast reset, beep/buzzer
 Auto power-off
 Orange backlight (-S option only)
 Low battery indicator
 Available Colors: White
 Operating Temperature: 10 – 40 C
 Environmental Humidity: 40 – 90%
 Batteries: 2 x AAA Alkaline (not included)

Certifications

CE, RoHS

Warranty Terms

12 months after delivery from factory.
 Defective units will be replaced free, customer only pays return shipping charges.

Packaging

Device Size: 98 x 38 x 17.2 mm
 Device Weight: 28g
 Package Dimensions: 14.9 x 9.7 x 3.3cm
 Carton Size: 50.5 x 36.5 x 32 cm , 100 pcs/ctn
 Carton Weight: GW/VW: 9.5 kg / 12.0 kg

BAT-2718 – High Accuracy Digital Breath Alcohol Tester With Temperature Sensor, Clock



High Accuracy hand-held tester with digital LCD provides precise readings.
 Detection / Display ranges:
 0.000 – 0.199% BAC, 0.000 – 2.000 ‰ BAC, 0.000 – 0.500 mg/l
 0.000 – 0.400% BAC, 0.000 – 4.000 ‰ BAC. 0.000 – 1.000 mg/l
 Result Display: % BAC, ‰ BAC, mg/l

Built in clock operates as real time clock, countdown timer.
 Temperature sensor
 Color: Black

Specifications

Display Type: 4-Digit LCD with Backlight
 Sensor Type: Hot-wire, Temperature
 Preheating Time: 15 seconds
 Test Opportunity Time: 10 seconds
 Detection / Display Range: See Above
 Retest after use: < 40 sec
 Clock functions: real time, countdown timer
 Low battery indicator
 Auto power-off
 Available Colors: Black
 Operating Temperature: 10 – 50 C
 Environmental Humidity (Operating): < 95%
 Batteries: 2 x AA Alkaline (not included)

Certifications

CE, RoHS

Warranty Terms

12 months after delivery from factory.
 Defective units will be replaced free, customer only pays return shipping charges.

Packaging

Device Size: 118 x 68 x 29 mm
 Device Weight: 90 g
 Package Dimensions:
 Carton Size: 60.5 x 33.5 x 55 cm , 60 pcs/ctn
 Carton Weight: NW/GW: 5.6 / 11 kg